

Hot Water, Efficiently







Features



Modern & Stylish A stylish slim line single piece unit incorporates a top-mounted compressor with compact footprint



Highly Efficient
Produces significantly
more heat energy than
the power input; saving
on purchased energy



Handy Controller Providing intuitive operation & helpful functions such as temp setting, timer & safety lock



Built in Frost Protection Protecting the condenser from icing for complete peace of mind

Smart Technology

Heat pumps utilise an ingenious technology to efficiently transfer thermal energy directly from the surrounding air and into the water, and so do not rely on direct sun or fossil fuels to provide an energy source.

Harvest the free energy from our plentiful air to

heat your water with the advanced Midea heat pump from Chromagen. This renewable energy

water heating technology uses up to 65% less

energy¹ than a conventional water heater, whilst

providing reliable hot water all day and night.




Did you know?

A heat pump is like an energy multiplier. From 1 kW of power input, it can create over 4 kW's of output heat². That's a performance efficiency of a remarkable 400%. Where as conventional electric storage water heaters car only convert 1 kW of input power into a maximum of 1 kW of output heat.

Energy Efficiency

Did you know?

Water heating accounts for nearly a quarter of the energy use and greenhouse gas emissions in the average Australian home.



*Estimation based on HP280 (RSJ-23/300RDN3-B) STC's in Zone 3 under medium load, obtained from independent laboratory test results and followed by TRNSYS modelling and a retail electricity cost of \$0.30c per kWh.

Heat Pump Selection

HP170

170L Capacity

No. of	Climate		
Persons	Cold	Warm	Hot
ŸŶ	170	170	170
ŸŶŶ	170	170	170
ŶŶŶŶ	280	170/280	170/280
****	280	280	280
*****	280	280	280

To be used as a guide only - based on typical usage of 45 litres of hot water per person thoughout the day.

HP170



HP280

280L Capacity



Smart Technology

With a Midea heat pump, set up and operation monitoring is made simple thanks to an amazing, in built user-friendly controller.

Operational modes

ECO (Heat Pump Only) mode: The standard mode where the highest efficiency is achieved

Hybrid Mode: The Heat Pump & E-heater operate together to ensure the set temperature is achieved

E-Heater: When the air temperature drops to below 5°C, the heat pump will automatically select E-heater mode for an electric hot water boost



Wide Operating Range

Operates as low as 5°C in ECO mode & between -20°C & 45°C with additional E-heat boost



Tank-Wrapped Condenser Coil

For efficient heat transfer & preventing water contamination



Low Operating Noise

Operating at a very low 48/49 dBA you will hardly know it's there!



Auto Disinfection[^]

Periodically heating the water beyond its set temp to prevent the growth of bacteria and legionella



Power Outage Memory Settings are retain

Settings are retained in the event of a power outage



How it Works

- A fan draws in air, containing heat energy, across the evaporator
- 2. The evaporator turns the liquid refrigerant into a gas
- 3. The compressor pressurises the refrigerant into a hot gas
- The hot gas inside the condenser coil heats the water inside the coil-wrapped tank
- The refrigerant reverts back to a liquid after heating the water and continues to the evaporator for the process to start again




EVAPORATOR

COMPRESSOR


STORAGE TANK

WATER

CONDENSER COIL



A heat pump provides a quick and easy replacement of your old energy-hungry electric water heater, whilst also reducing CO₂ emissions by over 4 tonnes, and saving you up to \$930* per year.



Residential Warranty

5 Year

Tank Cylinder (3 Year Labour) 3 Year Compressor (1 Year Labour)

1 Year
Electronics,
Parts & Labour

Additional warranties apply for Solar Victoria customers, please refer to separate warranty details online at chromagen.com.au/warranty.



Product Specifications





Heat Pump Model	HP170	HP280
Nominal volume capacity (L)	170	280
Voltage / Hz / Phase	220-240 / 50 / 1	220-240 / 50 / 1
Element input power (W)	2150	3000
Heating capacity - Heat Pump Only (W)	1500	2000
Max water temperature (°C)	65	60
Max rated input power (W) / current (A)	2780 / 12.1	4000 / 17.3
Relief valve pressure (kPa)	1000	1000
Noise level (dBA)	48	49
Net Weight (kg)	90	154
Pipe connection diameter (mm)	DN20	DN20
Cylinder Type	Vitreous Enamel	Vitreous Enamel
Outdoor resistance class	IP24	IP24
Operating Mode Function	Manual	Manual
Refrigerant type/quantity	R134a / 0.8kg	R134a / 1.6kg







Why choose Chromagen?

- o A leading provider of solar energy solutions with over 60 years history
- o Offices Australia wide with a national dealer & service network
- A wide range of energy efficient solutions to suit your lifestyle
- o Committed to quality, innovation & energy-efficient solutions



chromagen.com.au | 1300 367 565

Efficient Water Heaters | Solar Power Solutions | Air Conditioning